



25E

Technical Data | Metric



2.5t **PORTATA MASSIMA**
Max payload / Capacité maxi
Max Tragfähigkeit / Max capacidad

25E


INFORMAZIONI TECNICHE E DIMENSIONI D'INGOMBRO

Technical information and overall size

Informations techniques et taille globale

Technische information und Gesamte Größe

Información técnica y dimensiones totales



PORTATA MASSIMA

Max payload / Capacité maxi

2.500 kg

Max Tragfähigkeit / Max capacidad

PESO TOTALE

Total weight / Poids total

2.400 kg

Gesamtgewicht / Peso total

DIMENSIONI

Dimensions / Dimensions

2260 x 950 x 1685 mm

Abmessungen / Dimensiones

ANTERIORE

Front / Avant / Vorderrad / Delantera

N° 2 18 x 7 - 8"

POSTERIORE

Rear / Arrière / Hinterrad / Trasera

N° 1 300 x 135

IMPIANTO IDRAULICO

Hydraulics (Max pressure/Motor power)

Hydraulique (Pression maxi/Puissance moteur)

220 Bar – 4 kW AC

Hydraulik (Max Druck/Motorleistung)

Hidraulica (Presion max/Potencia motor)

TRAZIONE ANTERIORE

Front-wheel drive / À traction avant

1 x 3 kW AC

Frontantrieb / Tracción delantera

STERZATURA POSTERIORE

Rear steering / Direction arrière

700 W AC - 180°

Hintere Lenkung / Direccion trasera

BATTERIA

Battery / Batterie / Batterie / Batterie

48V - 200 Ah

CONTRAPPESO

Counterweights / Contrepoids

520 kg

Gegengewichte / Contrapesos

FRENI ELETTRICI

Electric brakes / Freins électriques / Elektrische Bremsen /Frenos eléctricos

25E


MASSIME PRESTAZIONI ED EQUIPAGGIAMENTI

Maximum performance and equipments

Maximum performances et équipement

Höchstleistung und Ausrüstung

Máximas prestaciones y equipamiento



NORMATIVE DI RIFERIMENTO

Reference standards / Normes de référence

Referenzstandards / Estandards de referencia

2006/42 CE
EN 13000

STANDARD

COMANDI

Controls / Commandes / Befehle / Comandos

GANCIO

Hook / Crochet / Haken / Gancho

TESTA AD INCLINAZIONE VARIABILE

Variable tilt head / Tête à inclinaison variable

Variabler Neigungskopf / Cabezal ajustable

RUOTE ANTI-TRACCIA

Non-marking tires / Roues non marquant

Non-Marking-Räder / Ruedas anti-marcas

OPTIONAL

ARGANO

Winch / Treuil / Winde / Cabrestante

JIB MANUALE

Manual jib / Flechette manuel / Manueller Ausleger / Pluma manual

RADIOCOMANDO PARTE AEREA

Radio control / Contrôle radio / Radio Kontrolle / Radio control

RIEMPIMENTO AUTOMATICO

Automatic refill / Recharge automatique de liquide

Automatische Nachfüllung / Recarga automatica de liquido

CARICA BATTERIE A BORDO

Onboard charger / Chargeur embarque / Bordladergerat / Cargadir a bordo

PIANALE DI CARICO

Carry deck / Plateforme de chargement

Ladeplattform / Plataforma de carga

ELETTROFRENI RUOTE ANTERIORI

Front electric brakes / Freins électriques avant

Elektrische Vorderradbremsen / Frenos eléctricos delanteros

BATTERIE AL LITIO

Lithium batteries / Batteries à lithium / Lithiumbatterien / Baterías de litio

TRASFORMAZIONE ATEX

ATEX transformation / Transformation ATEX

ATEX-Umwandlung / Transformación ATEX

VALLA CONNECT SYSTEM

info.valla@tadano.com

www.tadano.com

Tadano Ltd.

Kanda Square 18th Floor, 2-2-1 Kanda-Nishikicho, Chiyoda-ku, Tokyo 101-0054, Japan

Phone: +81-3-6811-7309 (International Division)

Manitex Valla S.R.L.

Via Leonardo da Vinci, 12 29016 - Careco - Piacenza - Italia.

Tel.: +39 0523 256411



Reaching new heights

