



V110R

Technical Data | Metric



11t

PORTATA MASSIMA

Max payload / Capacité maxi

Max Tragfähigkeit / Max capacidad

V110R


INFORMAZIONI TECNICHE E DIMENSIONI D'INGOMBRO

Technical information and overall size

Informations techniques et taille globale

Technische information und Gesamte Größe

Información técnica y dimensiones totales



PORTATA MASSIMA

Max payload / Capacité maxi

11.000 kg

Max Tragfähigkeit / Max capacidad

PESO TOTALE

Total weight / Poids total

11.400 kg

Gesamtgewicht / Peso total

DIMENSIONI

Dimensions / Dimensions

3765 x 1500 x 1945 mm

Abmessungen / Dimensiones

ANTERIORE

Front / Avant / Vorderrad / Delantera

N° 2 S.E. / 355/65 – 15"

POSTERIORE

Rear / Arrière / Hinterrad / Trasera

N° 2 S.E. / 250 – 15"

IMPIANTO IDRAULICO

Hydraulics (Max pressure/Motor power)

Hydraulique (Pression maxi/Puissance moteur)

220 Bar – 16 kW AC

Hydraulik (Max Druck/Motorleistung)

Hidraulica (Presion max/Potencia motor)

TRAZIONE ANTERIORE

Front-wheel drive / À traction avant

Frontantrieb / Tracción delantera

N° 2 x 6.5 kW AC

STERZATURA POSTERIORE

Rear steering / Direction arrière

Hintere Lenkung / Direccion trasera

800W AC - 180°

BATTERIA

Battery / Batterie / Batterie / Batterie

80V - 640 Ah

CONTRAPPESI REMOVIBILI

Removable counterweights / Contrepoids amovibles

Abnehmbare Gegengewichte / Contrapesos removibles

N° 2 x 2.100 kg

FRENI ELETTRIDRAULICI

Electro-hydraulic brakes / Freins électro-hydrauliques

Elektrohydraulische Bremsen / Frenos electrohidráulicos

V110R


MASSIME PRESTAZIONI ED EQUIPAGGIAMENTI

Maximum performance and equipments

Maximum performances et équipement

Höchstleistung und Ausrüstung

Máximas prestaciones y equipamiento



NORMATIVE DI RIFERIMENTO

Reference standards / Normes de référence

Referenzstandards / Estandards de referencia

2006/42 CE
EN 13000

STANDARD

RUOTE ANTI-TRACCIA

Non-marking tires / Roues non marquant

Non-Marking-Räder / Ruedas anti-marcas

TESTA AD INCLINAZIONE VARIABILE

Variable tilt head / Tête à inclinaison variable

Variabler Neigungskopf / Cabezal ajustable

RADIOCOMANDO

Radio-control / Radiocommande / Radio Kontrolle / Radio control

GANCIO

Hook / Crochet / Haken / Gancho

OPTIONAL

BARRA STABILIZZATRICE ANTERIORE

Stabilizer crossbar / Barre stabilisatrice

Vorderradabstützung / Barra estabilizadora

ARGANO

Winch / Treuil / Winde / Cabrestante

JIB MECCANICO RIPIEGABILE

Foldable mechanic jib / Flechette mécanique pliable

Klappbarer mechanischer Ausleger / Pluma mecanica plegable

JIB IDRAULICO RIPIEGABILE

Foldable hydraulic jib / Flechette hydraulique pliable

Klappbarer hydraulischer Ausleger / Pluma hidráulica plegable

FORCHE AUTOLIVELLANTI

Self-levelling forks / Fourches autonivelantes

Selbstnivellierende Gabeln / Horquillas autonivelantes

BATTERIE AL LITIO

Lithium batteries / Batteries à lithium

Lithiumbatterien / Baterías de litio

TRASFORMAZIONE ATEX

ATEX transformation / Transformation ATEX

ATEX-Umwandlung / Transformación ATEX

VALLA CONNECT SYSTEM

info.valla@tadano.com

www.tadano.com

Tadano Ltd.

Kanda Square 18th Floor, 2-2-1 Kanda-Nishikicho, Chiyoda-ku, Tokyo 101-0054, Japan

Phone: +81-3-6811-7309 (International Division)

Manitex Valla S.R.L.

Via Leonardo da Vinci, 12 29016 - Careco - Piacenza - Italia.

Tel.: +39 0523 256411



Reaching new heights

