



V46R

Technical Data | Metric



4.6t

PORTATA MASSIMA

Max payload / Capacité maxi

Max Tragfähigkeit / Max capacidad

V46R


INFORMAZIONI TECNICHE E DIMENSIONI D'INGOMBRO

Technical information and overall size

Informations techniques et taille globale

Technische information und Gesamte Größe

Información técnica y dimensiones totales



PORTATA MASSIMA

Max payload / Capacité maxi

4.600 kg

Max Tragfähigkeit / Max capacidad

PESO TOTALE

Total weight / Poids total

4.300 kg

Gesamtgewicht / Peso total

SBRACCIO MASSIMO

Max boom extension / Déport maximum

7,5 m

Maximale Auslegerverlängerung / Alcànce maximo

DIMENSIONI

Dimensions / Dimensions

2465 x 900 x 1560 mm

Abmessungen / Dimensiones

ANTERIORE

Front / Avant / Vorderrad / Delantera

N° 2 Cushion 22x8x16

POSTERIORE

Rear / Arrière / Hinterrad / Trasera

N° 2 Cushion 11x4x11 1/4

IMPIANTO IDRAULICO

Hydraulics (Max pressure/Motor power)

Hydraulique (Pression maxi/Puissance moteur)

220 Bar – 8 kW AC

Hydraulik (Max Druck/Motorleistung)

Hidraulica (Presion max/Potencia motor)

TRAZIONE ANTERIORE

Front-wheel drive / À traction avant

2x1,9 kW AC

Frontantrieb / Tracción delantera

STERZATURA POSTERIORE

Rear steering / Direction arrière

600 W AC - 180°

Hintere Lenkung / Direccion trasera

BATTERIA

Battery / Batterie / Batterie / Batterie

80V - 300 Ah

CONTRAPPESO

Counterweights / Contrepoids

1.430 kg

Gegengewichte / Contrapesos

FRENI ELETTRICI

Electro Brakes / Freins electro / ElektroBremse /Frenos electros

V46R


MASSIME PRESTAZIONI ED EQUIPAGGIAMENTI

Maximum performance and equipments

Maximum performances et équipement

Höchstleistung und Ausrüstung

Máximas prestaciones y equipamiento



NORMATIVE DI RIFERIMENTO

Reference standards / Normes de référence

Referenzstandards / Estandards de referencia

2006/42 CE - 2014/30 CE

2014/35 CE - 2000/14 CE

EN 13000

STANDARD

RUOTE ANTI-TRACCIA

Non-marking tires / Roues non marquant

Non-Marking-Räder / Ruedas anti-marcas

TESTA AD INCLINAZIONE VARIABILE

Variable tilt head / Tête à inclinaison variable

Variabler Neigungskopf / Cabezal ajustable

RADIOCOMANDO

Radio-control / Radiocommande / Radio Kontrolle / Radio control

GANCIO

Hook / Crochet / Haken / Gancho

OPTIONAL

ARGANO

Winch / Treuil / Winde / Cabrestante

JIB MECCANICO RIPIEGABILE

Foldable mechanic jib / Flechette mécanique pliable

Klappbarer mechanischer Ausleger / Pluma mecanica plegable

JIB IDRAULICO RIPIEGABILE

Foldable hydraulic jib / Flechette hydraulique pliable

Klappbarer hydraulischer Ausleger / Pluma hidráulica plegable

BATTERIE AL LITIO

Lithium batteries / Batteries à lithium

Lithiumbatterien / Baterías de litio

TRASFORMAZIONE ATEX

ATEX transformation / Transformation ATEX

ATEX-Umwandlung / Transformación ATEX

VALLA CONNECT SYSTEM

info.valla@tadano.com

www.tadano.com

Tadano Ltd.

Kanda Square 18th Floor, 2-2-1 Kanda-Nishikicho, Chiyoda-ku, Tokyo 101-0054, Japan

Phone: +81-3-6811-7309 (International Division)

Manitex Valla S.R.L.

Via Leonardo da Vinci, 12 29016 - Careco - Piacenza - Italia.

Tel.: +39 0523 256411



Reaching new heights

